



Maxime Rubber Tile

TECHNICAL DATA

Nominal Dimensions	24" (61 cm) x 24" (61 cm) x 1/4" (6.4 mm)
Finish	Hammered
ASTM F1344 - Rubber Floor Tile	Type 1 B, Grade 1
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, > 0.45 W/cm ²
ASTM E662 (NFPA 258) - Smoke Density	Passes, < 450
ASTM D2047 - Static Coefficient of Friction	> 0.60
ASTM F970 - Static Load Resistance	Passes less than .005" Indentation after 250 psi
ASTM F925 - Chemical Resistance	Excellent with chemicals listed in standard, Additional chemicals available via chart
ASTM E492/E989 - Impact Sound Transmission	IIC 60 (6" Concrete, Gypsum Drop Ceiling)
ASTM E90/E413 - Airborne Sound Transmission	STC 64 (6" Concrete, Gypsum Drop Ceiling)
ASTM E2179 - Effectiveness of Floor on Impact Sound Transmission	ΔIIC 16
Acclimation Time	48 Hours, see installation instructions for details
Service & Storage Temperature	65° - 85° F, see installation instructions for details

Sustainability Information	Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification* NSF/ANSI 332 Platinum Certification*
-----------------------------------	--

Warranty	5 Year for Weight Room or Athletic Applications 10 Year for Other Applications, see warranty document for details
-----------------	--

Recommended Adhesives	Excelsior AW-510, Wet-Set Acrylic Excelsior MS-700, Modified Silane Wet-Set Excelsior U-705, Urethane Wet-Set
------------------------------	---

Technical Support	solutions@rhctechnical.com
Product Support	support@procedoflooring.com
Technical Documentation	www.procedoflooring.com

*certificate or document available on website