



Versa Quartz European Collection

TECHNICAL DATA

| | |
|--|---|
| Nominal Dimensions | 12" (304.8 mm) x 12" (304.8 mm) x 0.080" (2 mm) Tile 24" (609.6 mm) x 24" (609.6 mm) x 0.080" (2 mm) Tile |
| Finish | Smooth, Urethane Factory Finish |
| ASTM F1066 - Vinyl Composition Tile | Exceeds Requirements |
| ASTM E648 (NFPA 253) - Critical Radiant Flux | Class 1, $\geq 0.45 \text{ W/cm}^2$ |
| ASTM E662 (NFPA 258) - Smoke Density | Passes, ≤ 450 |
| ASTM D2047 - Static Coefficient of Friction | ≥ 0.50 |
| ASTM F970 - Static Load Resistance | Passes, $\leq 0.005"$ Indentation after 250 psi |
| ASTM F970 - Static Load Resistance (Modified) | Passes, $\leq 0.005"$ Indentation after 3,500 psi |
| ASTM F925 - Chemical Resistance | Excellent with chemicals listed in standard, Additional chemicals available via chart |
| ASTM E2240 - Hardness | Shore D; ≥ 65 |
| ASTM D3389 - Abrasion Resistance | Excellent, $\leq 1 \text{ g}$ loss after 1,000 cycles |
| ASTM F1514 - Light Stability | Excellent, $\Delta E \leq 8$ |
| ASTM F1914 - Residual Indentation | Excellent, $\leq 8\%$ after 24 hour recovery |
| ASTM F2199 - Dimensional Stability | Excellent, $\leq 0.020"$ per linear foot |
| Acclimation Time | 48 Hours, see installation instructions for details |
| Service & Storage Temperature | 65° - 85° F, see installation instructions for details |
| Sustainability Information | Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification* NSF/ANSI 332 Platinum Certification* |
| Warranty | 20 Year, see warranty document for details |
| Recommended Adhesives | Excelsior SP-500, Pressure Sensitive Spray Excelsior AW-510, Wet-Set Acrylic Excelsior AP-520, Pressure Sensitive Roll/Trowel Excelsior MS-700, Modified Silane Wet-Set Excelsior U-705, Urethane Wet-Set |
| Technical Support | solutions@rhctechnical.com |
| Product Support | support@procedoflooring.com |
| Technical Documentation | www.procedoflooring.com |

*certificate or document available on website