



# Artisan Sculpted Wall Base

TECHNICAL DATA

<b>Nominal Dimensions</b>	<b>Canyon</b> 3" (76.2 mm) x 8' (2.44 m) x 3/8" (9.53 mm) <b>Synergy</b> 4 1/4" (107.95 mm) x 8' (2.44 m) x 1/4" (6.35 mm) <b>Bismark</b> 4 1/2" (114.3 mm) x 40' (12.19 m) x 3/8" (9.53 mm) <b>Polaris</b> 4 1/2" (114.3 mm) x 8' (2.44 m) x 3/8" (9.53 mm) <b>Structure</b> 4 1/2" (114.3 mm) x 8' (2.44 m) x 3/8" (9.53 mm) <b>Decatur</b> 4 5/8" (117.5 mm) x 8' (2.44 m) x 3/8" (9.53 mm) <b>Tempest</b> 5" (127 mm) x 8' (2.44 m) x 3/8" (9.53 mm) <b>Tungsten</b> 6" (139.7 mm) x 8' (2.44 m) x 1/4" (6.35 mm)
<b>ASTM F1861 - Resilient Wall Base</b>	Type TP, Group 2, Style D
<b>ASTM E648 (NFPA 253) - Critical Radiant Flux</b>	Class 1, $\geq 0.45$ W/cm <sup>2</sup>
<b>ASTM E662 (NFPA 258) - Smoke Density</b>	Passes, $\leq 450$
<b>ASTM E84 - Flammability</b>	Class A
<b>Acclimation Time</b>	48 Hours, see installation instructions for details
<b>Service &amp; Storage Temperature</b>	65° - 85° F, see installation instructions for details
<b>Sustainability Information</b>	Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification*
<b>Warranty</b>	2 Year, see warranty document for details
<b>Recommended Adhesives</b>	Excelsior WB-600, Acrylic Wall Base Excelsior C-630, Water Based Contact
<b>Technical Support</b>	<a href="mailto:solutions@rhctechnical.com">solutions@rhctechnical.com</a>
<b>Product Support</b>	<a href="mailto:support@procedoflooring.com">support@procedoflooring.com</a>
<b>Technical Documentation</b>	<a href="http://www.procedoflooring.com">www.procedoflooring.com</a>

\*certificate or document available on website