

<b>Nominal Dimensions</b>	18" (45.7 cm) x 18" (45.7 cm) x 1/8" (3.2 mm)
<b>Finish</b>	Smooth & Milled
<b>ASTM F1344 - Rubber Floor Tile</b>	Type 1 A & B, Grade 1
<b>ASTM E648 (NFPA 253) - Critical Radiant Flux</b>	Class 1, > 0.45 W/cm <sup>2</sup>
<b>ASTM E662 (NFPA 258) - Smoke Density</b>	Passes, < 450
<b>CAN/ULC-S102.2 - Surface Burning</b>	115 Flame Spread Rating 275 Smoke Developed Classification
<b>ASTM D2047 - Static Coefficient of Friction</b>	> 0.60
<b>ASTM F970 - Static Load Resistance</b>	Passes less than .005" Indentation after 250 psi
<b>ASTM F970 - Static Load Resistance (Modified)</b>	Passes less than .005" Indentation after 1100 psi
<b>ASTM F925 - Chemical Resistance</b>	Excellent with chemicals listed in standard, Additional chemicals available via chart
<b>ASTM F1514 - Heat Stability</b>	Excellent, ΔE < 8 average
<b>ASTM D3389 - Abrasion Resistance</b>	Excellent, < 1 g loss after 1000 cycles
<b>ASTM G21 - Resistance to Fungi</b>	Excellent, No Growth
<b>ASTM E492/E989 - Impact Sound Transmission</b>	IIC 51 (6" Concrete, Gypsum Drop Ceiling)
<b>ASTM E90/E413 - Airborne Sound Transmission</b>	STC 63 (6" Concrete, Gypsum Drop Ceiling)
<b>ASTM E2179 - Effectiveness of Floor on Impact Sound Transmission</b>	ΔIIC 9
<b>Acclimation Time</b>	48 Hours, see installation instructions for details
<b>Service &amp; Storage Temperature</b>	65° - 85° F, see installation instructions for details
<b>FloorScore Certification</b>	Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification*
<b>Warranty</b>	10 Year, see warranty document for details
<b>Recommended Adhesives</b>	Excelsior SP-500, Pressure Sensitive Spray Excelsior AW-510, Wet-Set Acrylic Excelsior AP-520, Pressure Sensitive Roll/Trowel Excelsior MS-700, Modified Silane Wet-Set Excelsior U-705, Urethane Wet-Set
<b>Technical Support</b>	<a href="mailto:solutions@rhctechnical.com">solutions@rhctechnical.com</a>
<b>Product Support</b>	<a href="mailto:support@procedoflooring.com">support@procedoflooring.com</a>
<b>Technical Documentation</b>	<a href="http://www.procedoflooring.com">www.procedoflooring.com</a>

\*certificate or document available on website