

<b>Available Lengths</b>	50' (15.24 m) Coil
<b>Height Dimensions</b>	7" (17.8 cm)
<b>Thickness Dimensions</b>	0.080" (0.20 cm)
<b>Finish</b>	Smooth with Coved Toe
<b>ASTM E648 (NFPA 253) - Critical Radiant Flux</b>	Class 1, $\geq 0.45 \text{ W/cm}^2$
<b>ASTM E662 (NFPA 258) - Smoke Density</b>	Passes, $\leq 450$
<b>ASTM F1514 - Heat Stability</b>	Passes, $\Delta E \leq 8$
<b>ASTM F1515 - Light Stability</b>	Passes, $\Delta E \leq 8$
<b>Acclimation Time</b>	48 Hours, see installation instructions for details
<b>Service &amp; Storage Temperature</b>	65° - 85° F, see installation instructions for details

<b>Sustainability Information</b>	Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification*
-----------------------------------	--

<b>Warranty</b>	5 Year, see warranty document for details
-----------------	---

<b>Recommended Adhesives</b>	Excelsior TP-620, Pressure Sensitive Tread Tape Excelsior EN-610, Epoxy Nose Filler Excelsior AW-510, Wet-Set Acrylic Excelsior C-630, Contact Adhesive Excelsior U-705, Urethane Wet-Set
------------------------------	---

<b>Technical Support</b>	<a href="mailto:solutions@rhctechnical.com">solutions@rhctechnical.com</a>
<b>Product Support</b>	<a href="mailto:support@procedoflooring.com">support@procedoflooring.com</a>
<b>Technical Documentation</b>	<a href="http://www.procedoflooring.com">www.procedoflooring.com</a>

\*certificate or document available on website

Vinyl Stair Treads are designed for use on all interior stairs, including pan-filled concrete steps and wooden steps. Roppe vinyl stair treads are non-conductive and resist scuffing, gouging and most chemicals and common substances.

