



Vinyl Stair Tread & Risers

TECHNICAL DATA

This document is intended to cover technical data for all Vinyl Stair Tread & Riser concepts for Procedo Flooring including Light Duty and Heavy Duty formats.

Nominal Dimensions	Various Lengths from 42" – 72" depending upon style
Finish	Ribbed
ASTM F2169 - Resilient Stair Treads	Type TP, Class 2, Group 1 & 2, Grade 1
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, $\geq 0.45 \text{ W/cm}^2$
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM D2047 - Static Coefficient of Friction	≥ 0.60
ASTM F1514 - Heat Stability	Passes, $\Delta E \leq 8$
ASTM F1515 - Light Stability	Passes, $\Delta E \leq 8$
Available Abrasive Strip Colors	Yellow, Black, White, & Glow in the Dark
Acclimation Time	48 Hours, see installation instructions for details
Service & Storage Temperature	65° - 85° F, see installation instructions for details
Sustainability Information	Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification*
Warranty	3 Year Light Duty 5 Year Heavy Duty, see warranty document for details
Recommended Adhesives	Excelsior TP-620, Pressure Sensitive Tread Tape Excelsior EN-610, Epoxy Nose Filler Excelsior AW-510, Wet-Set Acrylic Excelsior C-630, Contact Adhesive Excelsior U-705, Urethane Wet-Set
Technical Support	solutions@rhctechical.com
Product Support	support@procedoflooring.com
Technical Documentation	www.procedoflooring.com

*certificate or document available on website