



Thermoplastic Rubber Wall Base

TECHNICAL DATA

Nominal Dimensions	2 1/2" (63.5 mm) x 48" (1.22 m) x 1/8" (3.2 mm) 2 1/2" (63.5 mm) x 120' (36.58 m) x 1/8" (3.2 mm) 4" (101.6 mm) x 48" (1.22 m) x 1/8" (3.2 mm) 4" (101.6 mm) x 120' (36.58 m) x 1/8" (3.2 mm) 4 1/2" (114.3 mm) x 48" (1.22 m) x 1/8" (3.2 mm) 4 1/2" (114.3 mm) x 120' (36.58 m) x 1/8" (3.2 mm) 6" (152.1 mm) x 48" (1.22 m) x 1/8" (3.2 mm) 6" (152.1 mm) x 120' (36.58 m) x 1/8" (3.2 mm)
ASTM F1861 - Resilient Wall Base	Type TP, Group 2, Styles A & B
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, ≥ 0.45 W/cm ²
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM E84 - Flammability	Class A
CAN/ULC-S102.2 – Surface Burning	10 Flame Spread Rating 60 Smoke Developed Classification
Acclimation Time	48 Hours, see installation instructions for details
Service & Storage Temperature	65° - 85° F, see installation instructions for details
Sustainability Information	Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification*
Warranty	2 Year, see warranty document for details
Recommended Adhesives	Excelsior WB-600, Acrylic Wall Base Excelsior C-630, Water Based Contact
Technical Support	solutions@rhctechnical.com
Product Support	support@procedoflooring.com
Technical Documentation	www.procedoflooring.com

*certificate or document available on website