

| | |
|---|--|
| Nominal Dimensions | 2 1/2" (63.5 mm) x 48" (1.22 m) x 1/8" (3.2 mm) 2 1/2" (63.5 mm) x 120' (36.58 m) x 1/8" (3.2 mm) 4" (101.6 mm) x 48" (1.22 m) x 1/8" (3.2 mm) 4" (101.6 mm) x 120' (36.58 m) x 1/8" (3.2 mm) 6" (152.1 mm) x 48" (1.22 m) x 1/8" (3.2 mm) 6" (152.1 mm) x 120' (36.58 m) x 1/8" (3.2 mm) |
| ASTM F1861 - Resilient Wall Base | Type TV, Group 2, Styles A & B |
| ASTM E648 (NFPA 253) - Critical Radiant Flux | Class 1, ≥ 0.45 W/cm ² |
| ASTM E662 (NFPA 258) - Smoke Density | Passes, ≤ 450 |
| ASTM E84 - Flammability | Class A |
| CAN/ULC-S102.2 - Surface Burning | 10 Flame Spread Rating 60 Smoke Developed Classification |
| Acclimation Time | 48 Hours, see installation instructions for details |
| Service & Storage Temperature | 65° - 85° F, see installation instructions for details |
| Sustainability Information | Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification* |
| Warranty | 2 Year, see warranty document for details |
| Recommended Adhesives | Excelsior WB-600, Acrylic Wall Base Excelsior C-630, Water Based Contact |
| Technical Support | solutions@rhctechnical.com |
| Product Support | support@procedoflooring.com |
| Technical Documentation | www.procedoflooring.com |

*certificate or document available on website